

Superior Rubber Alloy Air Hose & Assemblies

Technical Data

The new superior rubber alloy hose comes from years of research and development to find the optimum compound used to manufacture a hose with the total feel and capabilities of a rubber hose but without the associated negative aspects.

- Braided reinforcement: high tensile polyester braid
- Highly flexible: excellent bend radius with anti-kink capabilities
- Durable: excellent abrasion resistance, plus oil and fuel resistant outer cover
- Silicone free
- Safe: highly visible green stripe for safety against becoming a trip hazard
- Ideal for outside: excellent ozone resistance, making it a number one choice for outdoor applications
- Smooth bore: consistent internal and external dimensions, with a smooth bore for optimum flow
- More Resistant: excellent resistance to oils and fuels
- Safety Factor: 3:1



Working Temperature: -20°C to +60°C

Hose can be ordered in various lengths.
Please contact Sales with your application requirements.

Maximum Working Pressure: 20 bar

30 Metre Coils			
PART NUMBER	I.D	I.D. mm	O.D.mm
SRAH06X	1/4"	6.3	14
SRAH08X	5/16"	8	17
SRAH10X	3/8"	10	19
SRAH13X	1/2"	12.5	23
SRAH19X	3/4"	19	30
SRAH25X	1"	25	37

100 Metre Coils			
PART NUMBER	I.D	I.D. mm	O.D.mm
SRAH06X-100	1/4"	6.3	14
SRAH08X-100	5/16"	8	17
SRAH10X-100	3/8"	10	19
SRAH13X-100	1/2"	12.5	23
SRAH19X-100	3/4"	19	30
SRAH25X-100	1"	25	37