# SAFETY DATA SHEET DE ICER



#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name DE ICER

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Deicer

#### 1.3. Details of the supplier of the safety data sheet

Supplier Arctic Hayes Ltd

Glover Way Leeds

West Yorkshire LS11 5JP

T+44 (0) 113 271 5245 www.arctic-hayes.com sales@arctic-hayes.com

#### 1.4. Emergency telephone number

Emergency telephone +44 (0)113 271 5245 (Monday to Thursday: 8:30am to 5pm - Friday: 8:30am to 4pm)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

**Health hazards** Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards Not Classified

Human health Gas or vapour is harmful on prolonged exposure or in high concentrations. In high

concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this

container is dangerous and can be fatal.

Environmental This product does not contain substances which are harmful to aquatic organisms or which

may cause long term effects to the aquatic environment

Physicochemical Aerosol containers can explode when heated, due to excessive pressure build-up. The

product is extremely flammable. When sprayed on a naked flame or any incandescent

material the aerosol vapours can be ignited.

## 2.2. Label elements

### Hazard pictograms





Signal word Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

## DE ICER

**Precautionary statements** P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe vapour/ spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with local regulations.

Contains PROPAN-2-OL

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

PROPAN-2-OL 30-60%

CAS number: 67-63-0 EC number: 200-661-7 REACH registration number: 01-

2119457558-25

Classification

Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336

### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

30-60%

Classification

Flam. Gas 1 - H220 Press. Gas (Liq.) - H280

ETHANEDIOL 1-5%

CAS number: 107-21-1 EC number: 203-473-3 REACH registration number: 01-

2119456816-28

Classification

Acute Tox. 4 - H302 STOT RE 2 - H373

### **DE ICER**

SODIUM NITRITE <1%

CAS number: 7632-00-0 EC number: 231-555-9 REACH registration number: 01-

2119471836-27

M factor (Acute) = 1

Classification

Ox. Sol. 3 - H272 Acute Tox. 3 - H301 Eye Irrit. 2 - H319 Aquatic Acute 1 - H400

The full text for all hazard statements is displayed in Section 16.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

**General information** Move affected person to fresh air at once.

Inhalation If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention

immediately.

**Ingestion** Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes.

### 4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

#### 5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. The product is highly flammable. Forms explosive

mixtures with air.

#### 5.3. Advice for firefighters

Protective actions during

firefighting

Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours.

### SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate.

Avoid inhalation of vapours.

### **DE ICER**

## 6.2. Environmental precautions

**Environmental precautions** Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with

sand, earth or other suitable non-combustible material.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near

spillage. Provide adequate ventilation. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. Absorb spillage

with non-combustible, absorbent material.

#### 6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions**Read and follow manufacturer's recommendations. Keep away from heat, sparks and open

flame. Do not spray on a naked flame or any incandescent material. Eliminate all sources of

ignition.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well

ventilated area. Pressurized container: protect from sunlight and do not expose to

temperatures exceeding 50°C. Do not pierce or burn, even after use.

### 7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

## Occupational exposure limits

#### PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m<sup>3</sup>

#### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup> Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

### **ETHANEDIOL**

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ particulate Long-term exposure limit (8-hour TWA): WEL 20 ppm 52 mg/m³ vapour Short-term exposure limit (15-minute): WEL 40 ppm 104 mg/m³ vapour Sk

#### **SODIUM NITRITE**

Long-term exposure limit (8-hour TWA): No std.

WEL = Workplace Exposure Limit. Sk = Can be absorbed through the skin.

**Ingredient comments** WEL = Workplace Exposure Limits

PROPAN-2-OL (CAS: 67-63-0)

### **DE ICER**

**DNEL** Industry - Dermal; Long term systemic effects: 888 mg/kg/day

Industry - Inhalation; Long term systemic effects: 500 mg/m³ Consumer - Dermal; Long term systemic effects: 319 mg/kg/day Consumer - Dermal; Long term systemic effects: 26 mg/kg/day Consumer - Inhalation; Long term systemic effects: 89 mg/m³

PNEC - Fresh water; 140.9 mg/l

marine water; 140.9 mg/l
Intermittent release; 140.9 mg/l
Sediment (Freshwater); 552 mg/kg
Sediment (Marinewater); 552 mg/kg

STP; 2251 mg/lSoil; 28 mg/kg

#### ETHANEDIOL (CAS: 107-21-1)

**DNEL** Industry - Inhalation; Short term : 35 mg/m<sup>3</sup>

Industry - Dermal; Long term : 106 mg/kg/day Consumer - Dermal; Long term : 53 mg/kg/day Consumer - Inhalation; Long term : 7 mg/m³

PNEC - Fresh water; 10 mg/l

marine water; 1 mg/lSoil; 1.53 mg/l

- STP; 199.5 mg/l

Sediment (Freshwater); 20.9 mg/lIntermittent release; 10 mg/l

#### 8.2. Exposure controls

#### Protective equipment



Appropriate engineering

controls

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any

occupational exposure limits for the product or ingredients.

Personal protection When using do not smoke.

**Eye/face protection** Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. The following protection should be worn: Chemical splash goggles.

**Hand protection** Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant,

impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough

time of the glove material.

Hygiene measures Wash hands after handling. Wash promptly if skin becomes contaminated. Wash at the end of

each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to

prevent drying of skin.

**Respiratory protection** If ventilation is inadequate, suitable respiratory protection must be worn.

#### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance Aerosol.

### **DE ICER**

Colour Clear.

Odour Organic solvents.

Flash point < -40°C

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 1.8% Upper flammable/explosive limit: 9.5%

Auto-ignition temperature 410-580°C

**Comments** Information given is applicable to the major ingredient.

9.2. Other information

Other information Not available.

Volatile organic compound This product contains a maximum VOC content of 550 g/litre.

#### SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** Stable at normal ambient temperatures and when used as recommended.

10.2. Chemical stability

**Stability** Avoid the following conditions: Heat, sparks, flames.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Does not decompose when used and stored as recommended.

#### 10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high

temperatures or direct sunlight.

## 10.5. Incompatible materials

Materials to avoid Keep away from oxidising materials, heat and flames.

## 10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or

vapours.

### SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity - oral

**ATE oral (mg/kg)** 13,235.29

General information Deliberately concentrating and inhaling the contents of this container is dangerous and can be

fatal.

**In high concentrations**, vapours and aerosol mists have a narcotic effect and may cause

headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.

Skin contact Skin irritation should not occur when used as recommended. Repeated exposure may cause

skin dryness or cracking.

Eye contact Irritating to eyes. Vapour or spray in the eyes may cause irritation and smarting. Repeated

exposure may cause chronic eye irritation.

### **DE ICER**

Acute and chronic health

hazards

Arrhythmia (deviation from normal heart beat). In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Route of exposure

Inhalation

Target organs

Central nervous system Respiratory system, lungs

Medical symptoms

Arrhythmia (deviation from normal heart beat). Narcotic effect. Vapours may cause

drowsiness and dizziness.

#### SECTION 12: Ecological information

**Ecotoxicity**No negative effects on the aquatic environment are known. The product is not expected to be

toxic to aquatic organisms.

12.1. Toxicity

**Toxicity** 

Not available.

#### 12.2. Persistence and degradability

Persistence and degradability Not available.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential Not available.

12.4. Mobility in soil

Mobility Not known.

#### 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

Not available.

12.6. Other adverse effects

Other adverse effects Not available.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

**General information** Do not puncture or incinerate, even when empty.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated

because of the risk of an explosion.

### **SECTION 14: Transport information**

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR

and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported

as Limited Quantities. Aerosols not so packed and labelled must show the following.

14.1. UN number

**UN No. (ADR/RID)** 1950

**UN No. (IMDG)** 1950

**UN No. (ICAO)** 1950

### **DE ICER**

**UN No. (ADN)** 1950

## 14.2. UN proper shipping name

Proper shipping name

**AEROSOLS** 

2.1

(ADR/RID)

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

### 14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

Transport labels



**ADN class** 

## 14.4. Packing group

ADR/RID packing group None

IMDG packing group None

ICAO packing group None

ADN packing group None

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

## 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

#### SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **DE ICER**

National regulations Control of Substances Hazardous to Health Regulations 2002 (as amended).

EH40/2005 Workplace exposure limits.

The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

**EU legislation** Commission Regulation (EU) No 2015/830 of 28 May 2015.

Guidance Workplace Exposure Limits EH40.

Safety Data Sheets for Substances and Preparations.

Approved Classification and Labelling Guide (Sixth edition) L131. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## **SECTION 16: Other information**

**Revision comments** Supplemental information added.

Revision date 07/10/2020

Revision 3

SDS number 10850

SDS status Approved.

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H229 Pressurised container: may burst if heated.

H272 May intensify fire; oxidiser.

H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed. H302 Harmful if swallowed. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

H400 Very toxic to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.