

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture  
Trade name : Painters Flexible Caulk Tr

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Professional use, Consumer use  
Use of the substance/mixture : Adhesives, sealants

#### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

Soudal N.V. N.V.  
Everdongenlaan 18-20  
2300 Turnhout  
Belgium  
T +32 14 42 42 31 - F +32 14 42 65 14  
[sds@soudal.com](mailto:sds@soudal.com) - [www.Soudal.com](http://www.Soudal.com)

### 1.4. Emergency telephone number

Emergency number : +32 14 58 45 45 (BIG)  
24h/24h

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

#### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.  
EUH210 - Safety data sheet available on request.

### 2.3. Other hazards

The product does not meet the PBT and vPvB classification criteria  
Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

Component	
1,2-benzisothiazol-3(2H)-one (2634-33-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

# Painters Flexible Caulk Tr

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60	< 0.05	Acute Tox. 4 (Oral), H302 Acute Tox. 2 (Inhalation:gas), H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS-No.: 55965-84-9 EC-No.: 611-341-5 EC Index-No.: 613-167-00-5 REACH-no: 01-2120764691-48	< 0.0015	Acute Tox. 2 (Inhalation), H330 Acute Tox. 2 (Dermal), H310 Acute Tox. 3 (Oral), H301 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60	( 0,05 ≤C < 100) Skin Sens. 1, H317
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS-No.: 55965-84-9 EC-No.: 611-341-5 EC Index-No.: 613-167-00-5 REACH-no: 01-2120764691-48	( 0,0015 ≤C ≤ 100) Skin Sens. 1A, H317 ( 0,06 ≤C < 0,6) Skin Irrit. 2, H315 ( 0,06 ≤C < 0,6) Eye Irrit. 2, H319 ( 0,6 ≤C ≤ 100) Eye Dam. 1, H318 ( 0,6 ≤C ≤ 100) Skin Corr. 1C, H314

Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Respiratory problems: consult a doctor/medical service.
First-aid measures after skin contact	: Wash skin with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophtalmologist if irritation persists.
First-aid measures after ingestion	: Rinse mouth out with water. Get medical advice/attention if you feel unwell.

# Painters Flexible Caulk Tr

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.  
Unsuitable extinguishing media : None known.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Large spills: scoop solid spill into closing containers. Clean contaminated surfaces with an excess of water. Wash clothing and equipment after handling.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Keep away from naked flames/heat.  
Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry area. Protect against frost. Keep container tightly closed.  
Incompatible products : Heat sources.  
Maximum storage period : 1 year  
Packaging materials : Synthetic material.

# Painters Flexible Caulk Tr

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

No additional information available

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

**Appropriate engineering controls:**

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

**Personal protective equipment symbol(s):**



##### 8.2.2.1. Eye and face protection

**Eye protection:**

Safety glasses

##### 8.2.2.2. Skin protection

**Skin and body protection:**

Wear suitable protective clothing

**Hand protection:**

Protective gloves

##### 8.2.2.3. Respiratory protection

**Respiratory protection:**

In case of insufficient ventilation, wear suitable respiratory equipment

##### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

**Environmental exposure controls:**

Avoid release to the environment.

# Painters Flexible Caulk Tr

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Variable.
Appearance	: Pasty.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not applicable
Boiling point	: Not available
Flammability	: Non flammable.
Explosive limits	: Not applicable
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not applicable
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 1,65 g/cm <sup>3</sup> (20°C)
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle characteristics	: Not applicable

#### 9.2. Other information

##### 9.2.1. Information with regard to physical hazard classes

No additional information available

##### 9.2.2. Other safety characteristics

VOC content : < 1 % (<16.5 g/l)

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Keep away from naked flames/heat.

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Painters Flexible Caulk Tr

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LD50 oral rat	490 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)	
LD50 oral rat	66 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Calculated by reference to active substance, Oral, 14 day(s))
LD50 oral	59 mg/kg bodyweight
LD50 dermal rat	> 141 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LD50 dermal	> 75 mg/kg bodyweight
LC50 Inhalation - Rat	0,17 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Calculated by reference to active substance, Inhalation (aerosol), 14 day(s))

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : Not classified  
Aspiration hazard : Not classified

Painters Flexible Caulk Tr	
Viscosity, kinematic	Not applicable

#### 11.2. Information on other hazards

No additional information available

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Not classified  
Not rapidly degradable

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LC50 - Fish [1]	2,18 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	2,94 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Experimental value, Lethal)

# Painters Flexible Caulk Tr

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
ErC50 algae	150 µg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Experimental value, GLP)

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)	
LC50 - Fish [1]	0,19 mg/l
EC50 - Crustacea [1]	0,007 mg/l (48 h, Acartia tonsa, Salt water, Experimental value, GLP)
EC50 - Other aquatic organisms [1]	0,126 mg/l waterflea
EC50 - Other aquatic organisms [2]	0,003 mg/l

### 12.2. Persistence and degradability

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
Persistence and degradability	Not biodegradable.

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)	
Persistence and degradability	Not biodegradable.

### 12.3. Bioaccumulative potential

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
BCF - Fish [1]	6,62 (Equivalent or similar to OECD 305, 56 day(s), Lepomis macrochirus, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	-0,9 – 0,99 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)	
BCF - Fish [1]	41 – 54 (OECD 305: Bioconcentration: Flow-Through Fish Test, 28 day(s), Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	0,75 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 24 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
Surface tension	72,6 mN/m (20 °C, 0.1 %, EU Method A.5: Surface tension)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0,97 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Ecology - soil	Highly mobile in soil.

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0,81 – 1 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

### 12.5. Results of PBT and vPvB assessment

Painters Flexible Caulk Tr	
The product does not meet the PBT and vPvB classification criteria	

# Painters Flexible Caulk Tr

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Non hazardous waste.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not discharge into drains or the environment.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 04 10 - waste adhesives and sealants other than those mentioned in 08 04 09 15 01 02 - plastic packaging

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID /

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.2. UN proper shipping name</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Not regulated

#### Transport by sea

Not regulated

#### Air transport

Not regulated

#### Inland waterway transport

Not regulated

#### Rail transport

Not regulated

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable



# Painters Flexible Caulk Tr

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

Contains substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

##### ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Sodium nitrate	7631-99-4	3102 50 00	ex 3824 99 96

Please see [https://ec.europa.eu/home-affairs/system/files/2021-11/list\\_of\\_competent\\_authorities\\_and\\_national\\_contact\\_points\\_en.pdf](https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf)

VOC content : < 1 % (<16.5 g/l)

Contains no substance subject to Regulation (EC) 273/2004 of the European Parliament and of the Council of 11 February 2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances.

##### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878		

#### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
-----	---

# Painters Flexible Caulk Tr

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
EUH208	Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
EUH210	Safety data sheet available on request.

# Painters Flexible Caulk Tr

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A

Safety Data Sheet (SDS), EU-20212

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.